



**T.C. Ticaret Bakanlığı**  
**İthalat Genel Müdürlüğü**  
**Sanayi Daireleri Başkanlıkları**

Değerli Sanayicilerimiz;

Bilindiği üzere, sanayicimizin ihtiyaç duyduğu **hammadde ve yarı mamul niteliğindeki** sanayi ürünlerine ilişkin her yıl 1 Ocak ve 1 Temmuz tarihlerinde yürürlüğe girecek şekilde yapılan askıya alma, üretim tüketimi karşılamayan ürünlerde ise kota başvuruları, ülkemiz temsilcilerinin de yer aldığı bir toplantıda Avrupa Komisyonu tarafından müzakere edilerek karara bağlanmaktadır.

Bu çerçevede, AB ya da Türk firmalarınca 01/01/2023 tarihinden itibaren gümrük vergilerinin askıya alınması veya tarife kontenjanı uygulanması talep edilen eşyaya ilişkin liste **ekte yer almaktadır**. Bu ürünlere ilişkin itirazların Bakanlığımıza **en geç 10/05/2022 tarihine kadar** intikal ettirilmesi gerekmektedir.

Başvuruların işleme konulabilmesi için en geç yukarıda belirtilen tarihe kadar Ticaret Bakanlığı'ndan evrak kayıt numarası almış olması gerekmektedir. İtirazlara ilişkin formlara <https://www.ticaret.gov.tr/ithalat/askiya-alma-ve-tarife-kontenjani/askiya-alma-sistemi> adresinden ulaşılabilir.

Bilgileri ile konunun firmalarımıza **ekteki listeye birlikte** duyurulması hususunda gereğini rica ederim.

Not: Askıya alma sistemine ilişkin detaylı bilgi için 2022/18 sayılı İthalat Tebliği incelenebilir. **Ayrıca firmalar tarafından listede yer alan ürünlerin özel tanımlı olmasından dolayı, GTP'den ziyade ürün tanımlarının incelenip, tanımlı karşılayacak üretimin bulunması durumunda başvuru yapılması önem arz etmektedir.**

Halil ÖZTÜRK  
Bakan a.  
Daire Başkanı

Kerim HEMDİL  
Bakan a.  
Daire Başkanı

Sinan YANAZ  
Bakan a.  
Daire Başkanı

İlgili Kişilerin İletişim Bilgileri:

Hammadde ve Ara mamul sektörleri için:

Muhammet HARTAVİ Uzman  
Özge SEZGİN Uzman

T: 0 312 204 95 84 E: [hartavim@ticaret.gov.tr](mailto:hartavim@ticaret.gov.tr)  
T: 0 312 204 99 25 E: [sezgino@ticaret.gov.tr](mailto:sezgino@ticaret.gov.tr)

Elektronik ve makina sektörleri için:

Fundagül BACI Uzman

T: 0 312 204 91 46 E: [bacif@ticaret.gov.tr](mailto:bacif@ticaret.gov.tr)

**CYCLE 2023-01**

Sorting order:

A – first 'quotas', then 'suspensions'

B – new requests, amending requests.

>>>The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic<<<<

| CN code    | TARIC | Reference Mail | Working Number | Description   | Quotas                            | New or amendment request | Measure status    | Partner Position Country | Partner Position | Public Comments  |
|------------|-------|----------------|----------------|---|-----------------------------------|--------------------------|-------------------|--------------------------|------------------|--|
| 2833 24 00 |       | 2206925/2022   | 1080           | Nickel Sulphate Hexahydrate (CAS RN 10101-97-0) with:<br>- a purity by weight of 99,9 % or more,<br>- a nickel content of 22,2 %, or more, but not more than 22,3 %, and<br>- a zinc content less than 1ppm | Q/25000tonnes , 01.01-31.12       | New                      | UNDER EXAMINATION | SE                       | Applicant        | Round 2023-1 used in the manufacture of precursors (metal hydroxide compounds) which form the basis of battery chemistries                                       |
| 2903 21 00 |       | 2258441/2022   | 1606           | Vinyl Chloride, Chloroethylene (Vinyl Chloride Monomer, VCM) (CAS RN 75-01-4)   | Q/75000000kil ograms, 01.01-31.12 | New                      | UNDER EXAMINATION | TR                       | Applicant        | Round 2023-01 Request for TR national quota.<br><br>used in various applications such as blow molding of bottles and containers, in the production of pipes etc. |
| 2916 11 00 |       | 1865073/2022   | 1089           | Acrylic acid (CAS RN 79-10-7) with a purity by weight of 99 % or more for use in the manufacture of goods of heading 3906 (1)   | Q/5000tonnes, 01.01-31.12         | New                      | UNDER EXAMINATION | FR                       | Applicant        | Round 2023-1 raw material for water treatment  |
| 2922 19 00 |       | 1865204/2022   | 1090           | 2-(Dimethylamino)ethyl acrylate (CAS RN 2439-35-2) with a purity by weight of 99 % or more  | Q/7000tonnes, 01.01-31.12         | New                      | UNDER EXAMINATION | FR                       | Applicant        | Round 2023-1 intermediate for the synthesis of a monomer used in the manufacture of  |

|            |  |              |      |  |  |     |                   |    |           |  |
|------------|--|--------------|------|--|--|-----|-------------------|----|-----------|--|
|            |  |              |      |  |  |     |                   |    |           | polymers intended for water treatment  |
| 2923 90 00 |  | 1956962/2022 | 1609 | Aqueous solution containing 78 % by weight or more of [2-(acryloyloxy)ethyl]trimethylammonium chloride (CAS RN 44992-01-0)   | <b>Q/10000tonnes , 01.01-31.12</b>         | New | UNDER EXAMINATION | FR | Applicant | Round 2023-01 used in the manufacturer of polymers intended for water treatment                                    |
| 3808 94 20 |  | 2059667/2022 | 1050 | Aqueous solution of the reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (CAS RN 55965-84-9) with a content of 13.0 – 15.2 %, stabilized by addition of Mg or Na salts  | <b>Q/1500tonnes, 01.01-31.12</b>           | New | UNDER EXAMINATION | DE | Applicant | Round 2023-1 used for the production of in-can preservatives   |
| 3911 90 11 |  | 2241389/2022 | 1604 | Containing by weight not less than 80 % of Poly(oxy-1,4-phenylenesulphonyl-1,4-phenyleneoxy-1,4-phenyleneisopropylidene-1,4-phenylene) (CAS 25154-01-2), in one of the forms mentioned in note 6(b) to Chapter 39  | <b>Q/6300tonnes, 01.01-31.12</b>           | New | UNDER EXAMINATION | BE | Applicant | Round 2023-01 additive   |
| 5603 14 10 |  | 2003624/2022 | 1608 | Reinforced polyester mat for manufacturing of waterproofing membranes (1)  | <b>Q/4700000square meters, 01.01-31.12</b> | New | UNDER EXAMINATION | ES | Applicant | Round 2023-01<br>Its use is that of armor for the manufacture of waterproofing asphalt membranes                   |
| 8501 31 00 |  | 2059389/2022 | 1049 | Electronic actuator consisting of <ul style="list-style-type: none"> <li>- a DC motor having a power of less than 600 W,</li> <li>- for usage with a supply voltage of 12 V to 48 V,</li> <li>- with motor connection (plug-in connection),</li> <li>- with contactless position sensor,</li> <li>- built in a rectangular housing of a width of less than 100 mm and a length of less than 150 mm or a cylindrical housing with a diameter of less than 100 mm, with reduction gear and lever attached to the motor drive shaft or</li> <li>- in a cylindrical housing with threads integrated into the rotor of the</li> </ul> | <b>Q/325000pieces, 01.01-31.12</b>         | New | UNDER EXAMINATION | DE | Applicant | Round 2023-1<br>Electronic actuator: component for control of turbo compressors of the kind used in motor vehicles |

|   |  |              |      |  |                                    |                  |                   |          |                      |  |
|---|--|--------------|------|--|------------------------------------|------------------|-------------------|----------|----------------------|--|
|   |  |              |      | motor for linear movement of the integrated control rod  |                                    |                  |                   |          |                      |  |
| 8501 31 00  |  | 1987247/2022 | 1051 | Electronic actuator consisting of <ul style="list-style-type: none"> <li>- a DC motor having a power of less than 600 W,</li> <li>- for usage with a supply voltage of 12 V to 48 V,</li> <li>- with motor connection (plug-in connection),</li> <li>- with contactless position sensor,</li> <li>- built in a rectangular housing of a width of less than 100 mm and a length of less than 150 mm or a cylindrical housing with a diameter of less than 100 mm, with reduction gear and lever attached to the motor drive shaft or</li> <li>- in a cylindrical housing with threads integrated into the rotor of the motor for linear movement of the integrated control rod</li> </ul> | <b>Q/100000pieces, 01.01-31.12</b> | <b>New</b>       | UNDER EXAMINATION | DE       | Applicant            | Round 2023-1<br>Electronic actuator: component for control of turbo compressors of the kind used in motor vehicles |
| ex 2401 10 35<br>ex 2401 10 70<br>ex 2401 10 95<br>ex 2401 10 95<br>ex 2401 20 35<br>ex 2401 20 70<br>ex 2401 20 95<br>ex 2401 20 95<br>ex 2401 20 95 | 91<br>10<br>11<br>21<br>91<br>91<br>10<br>11<br>21<br>91 |              | 0710 | Natural unmanufactured tobacco, whether or not cut in regular size, having a custom value of not less than EUR 450 per 100 kg net weight, for use as binder or wrapper for the manufacture of goods falling within subheading 2402 10 00 (1)   | <b>Q/6000tonnes, 01.01-31.12</b>   | <b>Amendment</b> | UNDER EXAMINATION | EU       | Applicant            | Round 2023-01-<br>Possible reduction of the quota amount to 3000t.   |
| ex 2918 29 00   | 75   | 2989075/2014 | 0703 | Octadecyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (CAS RN 2082-79-3) with: <ul style="list-style-type: none"> <li>- a sieve passing fraction at a mesh width of 500 µm of more than 99 % by weight, and</li> <li>- a melting point of 49 °C or more, but not more than 54 °C,</li> </ul> for use in the manufacture of PVC processing stabilizer-one packs based on powder mixtures (powders or press granulates)<br>(1)   | <b>Q/380tonnes, 01.01-31.12</b>    | <b>Amendment</b> | UNDER EXAMINATION | AT<br>DE | Applicant<br>Opposed | Round 2023-01 - roll over request for deletion.<br>Antioxidant for plastic products; acts in processing of PVC     |

|               |    |              |      |  |                             |           |                   |  |  |   |
|---------------|----|--------------|------|--|-----------------------------|-----------|-------------------|--|--|---|
| ex 2918 29 00 | 80 | 2989098/2014 | 0704 | Pentaerythritol tetrakis(3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) (CAS RN 6683-19-8) with:<br>- a sieve passing fraction at a mesh width of 250 µm of more than 75 % by weight and at a mesh width of 500 µm of more than 99 % by weight, and<br>- a melting point of 110 °C or more, but not more than 125 °C,<br>for use in the manufacture of PVC processing stabilizer-one packs based on powder mixtures (powders or press granulates)<br>(1) | Q/140tonnes, 01.01-31.12    | Amendment | UNDER EXAMINATION | AT<br>UK<br>DE                               | Applicant<br>Co-applicant<br>Opposed   | Round 2023-01 - roll over objection.<br>Antioxidant for plastic products; acts in processing of PVC   |
| ex 2920 29 00 | 70 | 3102835/2014 | 0707 | Tris (2,4-di-tert-butylphenyl)phosphite (CAS RN 31570-04-4)  | Q/6000tonnes, 01.01-31.12   | Amendment | UNDER EXAMINATION | UK<br>DE                                     | Applicant<br>Opposed   | Round 2023-01-roll over objection.<br>Polymer additives for the plastic industry  |
| ex 2921 41 00 | 10 | 816326/2014  | 0706 | Aniline (CAS RN 62-53-3) with a purity by weight of 99 % or more   | Q/150000tonnes, 01.01-31.12 | Amendment | UNDER EXAMINATION | HU<br>SK<br>DE<br>BE<br>DE<br>DE<br>DE       | Applicant<br>Applicant<br>Co-applicant<br>Opposed<br>Opposed<br>Opposed                    | Round 2023-01 - roll over objection.<br>Production of MDI products (methylene-diphenyl-diisocyanates).Polyuret hane systems to produce foams basically for thermal insulation and the automotive sector |
| ex 2922 41 00 | 20 | 2544706/2019 | 0702 | L-Lysine hydrochloride (CAS RN 657-27-2) or an aqueous solution of L-lysine (CAS RN 56-87-1), containing by weight 50 % or more of L-lysine  | Q/245000tonnes, 01.01-31.12 | Amendment | UNDER EXAMINATION | NL<br>AT<br>DK<br>ES<br>PL<br>FR<br>FR<br>FR | Applicant<br>Co-applicant<br>Co-applicant<br>Co-applicant<br>Opposed<br>Opposed<br>Opposed | Round 2023-01 -roll over request.<br>Animal feed, either in the form of a pre-mix or as a final product   |
| ex 2923 90 00 | 87 | 1709162/2020 | 0700 | 3-Chloro-2-hydroxypropyl)trimethylammonium chloride (CAS RN 3327-22-8), in the form of an aqueous solution containing by weight 65 % or more but not more than 71 % 3-chloro-2-hydroxypropyl)trimethylammonium chloride  | Q/19000tonnes , 01.01-31.12 | Amendment | UNDER EXAMINATION | FR<br>NL                                     | Applicant<br>Opposed   | Round 2023-01 - Objection.<br>It is used to make cationic starch  |

|                                |          |              |      |   |  |                  |                   |                      |  |   |
|--------------------------------|----------|--------------|------|---|--|------------------|-------------------|----------------------|--|---|
| ex 2924 19 00                  | 85       | 385030/2013  | 0709 | 3-Iodoprop-2-yn-1-yl butylcarbamate (CAS RN 55406-53-6)   | <b>Q/275tonnes, 01.07-31.12</b>        | <b>Amendment</b> | UNDER EXAMINATION | NL<br>NL<br>NL       | Applicant<br>Opposed<br>Opposed                    | Round 2023-01 - roll over objection. Used to produce biocides   |
| ex 2933 39 99                  | 43       | 846862/2014  | 0705 | 2,2,6,6-Tetramethylpiperidin-4-ol (CAS RN 2403-88-5)  | <b>Q/1000tonnes, 01.01-31.12</b>       | <b>Amendment</b> | UNDER EXAMINATION | IT<br>DE             | Applicant<br>Opposed                               | Round 2023-01 - roll over objection used exclusively as an intermediate in synthesis of light stabilizer 'HALS' (Hindered Amine Light-Stabiliser) for plastics  |
| ex 3911 90 19                  | 10       | 1450/7/1995  | 0708 | <b>BE(new text proposal):</b><br>Containing by weight not less than 80 % of Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4'-biphenylene) (CAS 25608-64-4)<br>-----<br><b>Current description</b><br>Poly(oxy-1,4-phenylenesulphonyl-1,4-phenyleneoxy-4,4'-biphenylene)               | <b>Q/5000tonnes, 01.01-31.12</b>       | <b>Amendment</b> | UNDER EXAMINATION | BE<br>LU<br>DE<br>DE | Co-applicant<br>Co-applicant<br>Opposed<br>Opposed | Round 2023-01 - roll over request.  |
| ex 8482 99 00                  | 50       | 4921841/2020 | 0713 | Inner and outer rings made of steel, not grinded, outer ring with an internal raceway, inner ring with an external raceway, with external diameters of:<br>- 14 mm or more but not more than 77 mm for the inner ring, and<br>- 26 mm or more but not more than 101 mm for the outer ring | <b>Q/1000000kilograms, 01.01-01.07</b> | <b>Amendment</b> | UNDER EXAMINATION | PT<br>TR             | Applicant<br>Opposed                               | Round 2023-01 - Roll over request. Round 2022-07 - The suspension with serial number 0.8088 will be set to deleted. A quota will open for the period 01.07-31.12.2022, with quota volume - 10 million kg. Round 2021-07 of a kind used for the production of one raceway ball bearing |
| ex 8501 40 20<br>ex 8501 40 80 | 40<br>30 | 1037/2007    | 0701 | <b>DE(11.03.2022) request for amendment:</b><br>Electric AC commutator motor, single-phase,<br>- also with an nominal output of 180 W or more,<br>- an input power of 150 W or more but not more than 2 700 W,  | <b>Q/2000000pieces, 01.01-31.12</b>    | <b>Amendment</b> | UNDER EXAMINATION | HU                   | Applicant  | Round 2023-01 - request for amendment.  |

|            |  |                 |      |   |                                     |                  |                   |    |           |  |
|------------|--|-----------------|------|---|-------------------------------------|------------------|-------------------|----|-----------|--|
|            |  |                 |      | <ul style="list-style-type: none"> <li>- an external diameter of more than 120 mm (<math>\pm 0,2</math> mm) but not more than 135 mm (<math>\pm 0,2</math> mm),</li> <li>- a rated speed of more than 10 000 rpm but not more than 50 000 rpm,</li> <li>- also equipped with air-inducting ventilator,</li> <li>- also with mechanical device (pinion, screws, gear connection etc.) on the shaft</li> </ul> <p>for use in the manufacture of vacuum cleaners or domestic appliances</p> <p>---</p> <p><b>Current description:</b><br/>Electric AC commutator motor, single-phase, with an output of 250 W or more, an input power of 700 W or more but not more than 2 700 W, an external diameter of more than 120 mm (<math>\pm 0,2</math> mm) but not more than 135 mm (<math>\pm 0,2</math> mm), a rated speed of more than 30 000 rpm but not more than 50 000 rpm, equipped with air-inducting ventilator, for use in the manufacture of vacuum cleaners<br/>(1)</p> |                                     |                  |                   |    |           |  |
| 9503 00 75 |  | 4814991/2020 TR | 0711 | <p>Printed circuit boards in a square or rectangular shape with:</p> <ul style="list-style-type: none"> <li>- a body made of plastic,</li> <li>- a potentiometer on the front side which provides voltage control,</li> <li>- coloured cables which are connected to the circuit boards for transmitting commands,</li> </ul> <p>for use in the manufacture of toys (cars)<br/>(1)</p>  | <b>Q/5000000pieces, 01.01-31.12</b> | <b>Amendment</b> | UNDER EXAMINATION | TR | Applicant | <p>Round 2023-01 - request for increase of TR national quota.</p> <p>Printed circuit boards for toy cars and their controllers</p>   |
| 9503 00 95 |  | 4814935/2020    | 0712 | <p>Sound mechanism with:</p> <ul style="list-style-type: none"> <li>- a body made of plastic (generally in flesh color),</li> <li>- speaker holes on top of the body,</li> <li>- an insulation tape at the bottom of the body,</li> <li>- a mechanism which works with pressing top of the body after the insulation tape is removed,</li> </ul>  | <b>Q/3000000pieces, 01.01-31.12</b> | <b>Amendment</b> | UNDER EXAMINATION | TR | Applicant | <p>Round 2023-01 - request for increase of TR national quota.</p> <p>Sound mechanisms for use in the manufacture of toys (dolls)</p> |

|  |  |  |  |   |  |  |  |  |  |  |
|--|--|--|--|---|--|--|--|--|--|--|
|  |  |  |  | - previously loaded voices to play upon pressing the button, for use in the manufacture of toys (dolls) (1) |  |  |  |  |  |  |
|--|--|--|--|---|--|--|--|--|--|--|

| CN code    | TARIC | Reference Mail | Working Number | Description  | Suspensions | New or amendment request | Measure status    | Partner Position Country | Partner Position          | Public Comments  |
|------------|-------|----------------|----------------|--|-------------|--------------------------|-------------------|--------------------------|---------------------------|--|
| 1518 00 99 |       | 2241226/2022   | 1602           | Mix of:<br>- oil from palm mill effluents. "Crude Oil, ISCC Certified, from Condensation Process of Fresh Fruit Bunches (FFB'S)/ Palm Oil Mill Effluent Oil", and<br>- oil from the pressing of empty fruits of palm oil, "Crude Oil, ISCC Certified, from Empty Fruit Bunch Pressing Process - EFB" | S           | New                      | UNDER EXAMINATION | ES                       | Applicant                 | Round 2023-01 used as raw material for the manufacture of biofuels               |
| 1518 00 99 |       | 2206803/2022   | 1079           | Unfit for consumption mixtures of vegetable oils – Used cooking oil (Used cooking oil – UCO), for the purpose of producing biodiesel   | S           | New                      | UNDER EXAMINATION | BG                       | Applicant                 | Round 2023/1 intended use of the imported product is for production of biodiesel |
| 2309 90 31 |       | 2056217/2022   | 1047           | Feed additive, consisting of :<br>- 55 % L-Lysine (+/- 1 %),<br>- 19 % Sulphate,<br>- 5 % carbohydrates, of which 0,5 % or more as starch, and<br>- 21 % other ingredients   | S           | New                      | UNDER EXAMINATION | DE                       | Applicant                 | Round 2023/1 Intended use: Feed Additive   |
| 2309 90 31 |       | 1995474/2022   | 1039           | Lysine sulphate containing by weight 54 % or more lysine on dry matter basis   | S           | New                      | UNDER EXAMINATION | NL<br>DK                 | Applicant<br>Co-applicant | Round 2023/1 to produce a premix or a complete feed                              |
| 2818 10 91 |       | 2207627/2022   | 1088           | Sintered corundum with a micro crystalline structure, consisting of aluminium oxide (CAS RN 1344-28-1) and magnesium aluminate (CAS RN 12068-51-8), with a content by weight (calculated as oxides) of:<br>- 92 % or more, but not more than 94 % of aluminium oxide, and                            | S           | New                      | UNDER EXAMINATION | AT                       | Applicant                 | Round 2023/1 used to produce ceramic grinding wheels                             |



|            |  |              |      |   |   |     |                   |    |           |   |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
|            |  |              |      | - 7 % ( $\pm$ 1 %) of magnesium oxidewith less than 50 % of the total weight having a particle size of more than 10 mm                    |   |     |                   |    |           |   |
| 2845 90 10 |  | 1848300/2022 | 2018 | (1S)-1-{3-Chloro-5-fluoro-2-[(4-methoxyphenoxy)methyl]phenyl}-1-deuterio-ethanamine hydrochloride with a purity by weight of 98 % or more | S | New | UNDER EXAMINATION | ES | Applicant | Round 2023/1<br><br>for use in the manufacturing of a new Active Pharmaceutical Ingredient.                 |
| 2845 90 90 |  | 2213712/2022 | 1600 | Ytterbium oxide, enriched with 99,0 % or more but not more than 99,8 % of Ytterbium-176 (CAS RN 1380743-42-9)                             | S | New | UNDER EXAMINATION | DE | Applicant | Round 2023-01 used in particular in the field of medical therapy, for producing medicament.                 |
| 2903 69 19 |  | 1476668/2022 | 1003 | Vinyl bromide (CAS RN 593-60-2) with a purity by weight of 98 % or more   | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 it is employed in the synthesis of the APIs  |
| 2905 39 95 |  | 1965501/2022 | 1034 | 1,5-Pentanediol (CAS RN 111-29-5) with a purity by weight of 97 % or more   | S | New | UNDER EXAMINATION | DE | Applicant | Round 2023/1 Mode of operation: Synthesis building block<br>Production of polymers and surface coatings     |
| 2912 49 00 |  | 1775603/2022 | 1013 | 4-Difluoromethoxy-3-hydroxybenzaldehyde (CAS RN 151103-08-1) with a purity by weight of 98 % or more                                      | S | New | UNDER EXAMINATION | ES | Applicant | Round 2023/1 an intermediate of synthesis used in the manufacturing process of the active ingredient        |
| 2914 50 00 |  | 1476718/2022 | 1004 | 1-(5-Fluoro-2-hydroxyphenyl)-2-(3-fluorophenyl)ethan-1-one (CAS RN 1300582-07-3) with a purity by weight of 98 % or more                  | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 it is an active ingredient   |
| 2914 79 00 |  | 1804900/2022 | 2005 | (4R)-4-(2-Fluorophenyl)-3,4-dihydro-2H-naphthalen-1-one (CAS RN 1234356-88-7) with a purity by weight of 99 % or more                     | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 raw material in the chemical synthesis for the production of active pharmaceutical ingredients |

|            |  |              |      |   |   |     |                   |    |           |   |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
| 2915 90 70 |  | 2207539/2022 | 1086 | Trifluoroacetic anhydride (CAS RN 407-25-0) with a purity by weight of 98 % or more   | S | New | UNDER EXAMINATION | AT | Applicant | Round 2023/1 used as raw material for the manufacturing of pharmaceutical intermediates   |
| 2916 20 00 |  | 1804642/2022 | 2003 | Methyl 2,2-dimethyl-3-(2-methylprop-1-en-1-yl)cyclopropane-1-carboxylate (CAS RN 5460-63-9) with a purity by weight of 90 % or more | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 reagent/intermediate for the synthesis of insecticides   |
| 2916 20 00 |  | 1816669/2022 | 2013 | Tefluthrin (CAS RN 79538-32-2) with a purity by weight of 96,5 % or more  | S | New | UNDER EXAMINATION | BE | Applicant | Round 2023/1 for use in the production of insecticides  |
| 2916 39 90 |  | 1965554/2022 | 1033 | Nitrobenzoic acid (CAS RN 62-23-7) with a purity by weight of 99 % or more  | S | New | UNDER EXAMINATION | DE | Applicant | Round 2023/1 Mode of operation: Synthesis building block Production of light stabilizers  |
| 2918 19 98 |  | 1479088/2022 | 1007 | (R)-2-benzyloxypropanoic acid (CAS RN 100836-85-9) with a purity by weight of 98 % or more  | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 an active ingredient that will be for the manufacture of drug for the treatment of marginal zone lymphoma and follicular lymphoma. |
| 2918 19 98 |  | 2207503/2022 | 1085 | Rac-tert-butyl 3-hydroxy-4-pentenoate (CAS No 122763-67-1) with a purity by weight of 98 % or more                                  | S | New | UNDER EXAMINATION | AT | Applicant | Round 2023/1 used as an intermediate in the production of an active pharmaceutical ingredient.  |
| 2918 30 00 |  | 1884119/2022 | 1020 | Methyl 2-((1S,2R)-3-oxo-2-pentylcyclopentyl)acetate (CAS RN 93452-03-0), with a purity by weight of 99 % or more                    | S | New | UNDER EXAMINATION | FR | Applicant | Round 2023/1 FOR THE MANUFACTURING OF: Fragrances   |
| 2918 30 00 |  | 1995256/2022 | 1038 | Methyl (3-oxo-2-pentylcyclopentyl)acetate (CAS RN 24851-98-7), with a purity by weight of 99 % or more                              | S | New | UNDER EXAMINATION | FR | Applicant | Round 2023/1 INTENDED USE: PERFUME INTERMEDIARIES   |

## Gelen Tarih Sayı: 12/04/2022 - 1153

|            |  |              |      |  |   |     |                   |    |           |   |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|---|
| 2921 43 00 |  | 2260292/2022 | 1607 | 6-Chloro- $\alpha,\alpha,\alpha$ -trifluoro-m-toluidine (CAS RN 121-50-6) with a purity by weight of 98 % or more  | S | New | UNDER EXAMINATION | CZ | Applicant | Round 2023-01 Raw material for production of other chemical compounds                                       |
| 2922 19 00 |  | 1804695/2022 | 2004 | 2-Methoxyethan-1-amine (CAS RN 109-85-3) with a purity by weight of 98 % or more   | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 raw material in the chemical synthesis for the production of active pharmaceutical ingredients |
| 2922 49 85 |  | 1805020/2022 | 2007 | (S)-ethyl 3-amino-3-phenylpropanoate hemi((2R,3R)-2,3-dihydroxysuccinate)(CAS NR N/A) with a purity by weight of 98 % or more                            | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 a substance for use in pharmaceutical industry   |
| 2922 50 00 |  | 2041028/2022 | 1045 | (3R)-N-(tert-butoxycarbonyl)-3-amino-4-(2,4,5-trifluorophenyl)butanoic acid (CAS No 486460-00-8) with a purity by weight of 97 % or more                 | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 Raw material used in the synthesis of active pharmaceutical substance                          |
| 2922 50 00 |  | 1848412/2022 | 2020 | 1-{{4-(Benzyloxy)phenyl}-2-(dimethylamino)ethyl} cyclohexanol (CAS 93413-61-7) with a purity by weight of 98 % or more                                   | S | New | UNDER EXAMINATION | ES | Applicant | Round 2023/1 for use in the manufacturing of basic pharmaceutical compounds                                 |
| 2922 50 00 |  | 1578722/2022 | 1010 | [4-[2-(Dimethylamino)ethoxy]phenyl][4-hydroxyphenyl]methanone (CAS RN 173163-13-8) with a purity by weight of 98 % or more                               | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 used for the production of a drug for the treatment of breast health                           |
| 2924 19 00 |  | 2241309/2022 | 1603 | Propamocarb hydrochloride (CAS RN 25606-41-1) with a purity of 66,5 % by weight  | S | New | UNDER EXAMINATION | BE | Applicant | Round 2023-01 used as fungicide, for the specific control of phycomycetous diseases                         |
| 2924 19 00 |  | 1884193/2022 | 1019 | N,N-Dimethyldecane-1-amide (CAS RN 14433-76-2) with a purity by weight of 99 % or more   | S | New | UNDER EXAMINATION | BE | Applicant | Round 2023/1 is used in agriculture for as fungicide production   |
| 2924 29 70 |  | 1807814/2022 | 2009 | Carbamic acid, N-[(1R,2S,5S)-2-amino-5-[(dimethylamino)carbonyl]cyclohexyl]-, 1,1-dimethylethyl ester, ethanedioate (1:1) (CAS NR 1210348-34-7 or CAS NR | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 to be used in the synthesis of intermediates and   |

## Gelen Tarih Sayı: 12/04/2022 - 1153

|            |  |              |      |  |   |     |                   |    |           |   |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|---|
|            |  |              |      | 929693-32-3) with a purity by weight of 95 % or more   |   |     |                   |    |           | active pharmaceutical ingredients   |
| 2924 29 70 |  | 1848369/2022 | 2019 | 2-[4-(Benzyloxy)phenyl]-N,N-dimethylacetamide (CAS 919475-15-3) with a purity by weight of 98 % or more  | S | New | UNDER EXAMINATION | ES | Applicant | Round 2023/1 for use in manufacturing of basic pharmaceutical compounds   |
| 2924 29 70 |  | 1777549/2022 | 2001 | tert-Butyl N-[(1R,2S,5S)-2-amino-5-(dimethylcarbamoyl)cyclohexyl]carbamate, oxalic acid (1:1) (CAS RN 1210348-34-7), having a purity by weight equal to or greater than 95,0 % | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1<br>A chemical product to be used in the pharmaceutical industry  |
| 2924 29 70 |  | 1180369/2022 | 1000 | Valifenalate (ISO) (CAS RN 283159-90-0) with a purity by weight of 98 % or more  | S | New | UNDER EXAMINATION | BE | Applicant | 2023/1 used as base for pesticides mixture to be used in agricultural crops   |
| 2925 29 00 |  | 1804964/2022 | 2006 | 1-(3-(2-Hydroxyethyl)phenyl)guanidinium methanesulfonate (CAS RN 2101429-50-7) with a purity by weight of 99 % or more   | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 raw material in the chemical synthesis for the production of active pharmaceutical ingredients   |
| 2926 90 70 |  | 1477700/2022 | 1006 | 3-Bromo-6-chloro-2-fluorobenzonitrile (CAS RN 943830-79-3) with a purity by weight of 98 % or more   | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 an active ingredient that will be used for the preparation of a drug to treat HIV.   |
| 2931 90 00 |  | 1476546/2022 | 1001 | 2-(Trimethylsilyl)ethoxymethyl chloride (CAS RN 76513-69-4) with a purity by weight of 98 % or more  | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 used as an active ingredient currently in the clinical phase for the treatment of the following diseases: COVID-19, prostate cancer, breast cancer, triple negative breast cancer (TNBC) |
| 2932 99 00 |  | 2059115/2022 | 1048 | Diosgenin (CAS RN 512-04-9) with a purity by weight of 95 % or more  | S | New | UNDER EXAMINATION | DE | Applicant | Round 2023/1 for the production of lipids   |

## Gelen Tarih Sayı: 12/04/2022 - 1153

|            |  |              |      |  |   |     |                   |       |                        |  |
|------------|--|--------------|------|--|---|-----|-------------------|-------|------------------------|--|
| 2933 19 90 |  | 1476856/2022 | 1005 | 5-Amino-3-(3-fluoro-4-isopropoxyphenyl)-1H-pyrazole-4-carbonitrile (CAS RN N/A) with a purity by weight of 98 % or more  | S | New | UNDER EXAMINATION | IT    | Applicant              | Round 2023/1 for the manufacture of drug for the treatment of marginal zone lymphoma and follicular lymphoma             |
| 2933 19 90 |  | 1818173/2022 | 2014 | 4,5-Dimethyl-1H-pyrazole-3-carboxylic acid (CAS: 89831-40-3) with a purity by weight of 98 % or more   | S | New | UNDER EXAMINATION | ES    | Applicant              | Round 2023/1 for used in the manufacturing of a new Active Pharmaceutical Ingredient                                     |
| 2933 39 99 |  | 1818301/2022 | 2015 | 2-hydroxypyridine-N-oxide (CAS: 13161-30-3) with a purity by weight of 98 % or more  | S | New | UNDER EXAMINATION | ES AT | Applicant Co-applicant | Round 2023/1 for use in the manufacturing of a new Active Pharmaceutical Ingredient                                      |
| 2933 39 99 |  | 1804595/2022 | 2002 | 2-Phenyl-2-(2-pyridyl)acetamide (CAS RN 7251-52-7) with a purity by weight of 98 % or more   | S | New | UNDER EXAMINATION | IT    | Applicant              | Round 2023/1 to be used in pharmaceutical industry for the production of a drug  |
| 2933 39 99 |  | 1775777/2022 | 1014 | N-(5-bromo-3-methylpyridin-2-YL)-N-methylbenzamide (CAS RN 446299-80-5) with a purity by weight of 98 % or more  | S | New | UNDER EXAMINATION | ES    | Applicant              | Round 2023/1 intermediate of synthesis used in the manufacturing process of the active ingredient                        |
| 2933 39 99 |  | 1957248/2022 | 1031 | Octadecanoic acid, methyl ester, reaction products with 1-(2-hydroxy-2-methylpropoxy)-2,2,6,6-tetramethyl-4-piperidinol (CAS RN 300711-92-6) with a purity by weight of 95 GHT or more | S | New | UNDER EXAMINATION | DE    | Applicant              | Round 2023/1 Mode of operation: light stabilizer Production of plastics that are particularly weather-resistant outdoors |
| 2933 39 99 |  | 2207405/2022 | 1083 | 3-Hydroxypyridine (CAS No 109-00-2) with a purity by weight of 98 % or more  | S | New | UNDER EXAMINATION | AT    | Applicant              | Round 2023/1 material in the production of an active pharmaceutical ingredient   |

## Gelen Tarih Sayı: 12/04/2022 - 1153

|            |  |              |      |   |   |     |                   |    |           |   |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
| 2933 39 99 |  | 2200068/2022 | 1074 | 2-Hydroxypyridine 1-oxide (HOPO) (CAS RN 13161-30-3) with a purity by weight of 98 % or more  | S | New | UNDER EXAMINATION | AT | Applicant | Round 2023/1 used as raw material for the manufacturing of pharmaceutical intermediates   |
| 2933 49 90 |  | 1848220/2022 | 2017 | 2-Methyl-4-(1-methyl-1H-1,2,4-triazol-5-yl)quinolin-8-ol (CAS: 1174132-59-2) with a purity by weight of 98 % or more  | S | New | UNDER EXAMINATION | ES | Applicant | Round 2023/1  |
| 2933 59 95 |  | 1995622/2022 | 1040 | Sotorasib (INN) (CAS RN 2296729-00-3) with a purity by weight of 99 % or more   | S | New | UNDER EXAMINATION | SI | Applicant | Round 2023/1 active pharmaceutical ingredients (APIs) exclusively for the use in production of medicinal products for human use             |
| 2933 69 80 |  | 1974383/2022 | 1035 | 1,3-propanediamine, N1,N1'-1,2-ethanediyilbis-, reaction product with cyclohexane and peroxidized N-butyl-2,2,6,6-tetramethyl-4-piperidinamine-2,4,6-trichlor-1,3,5-triazine (CAS RN 191680-81-6) with a purity of 97 % by weight | S | New | UNDER EXAMINATION | DE | Applicant | Round 2023/1 Intended use: flame retardants, light stabilizers, thermal stabilizers<br>Manufacture of fibers and films based on polyolefins |
| 2933 71 00 |  | 2258272/2022 | 1605 | Epsilon-kaprolaktam/ 6 heksone-laktam/ ε-caprolactam (CAS RN 105-60-2)  | S | New | UNDER EXAMINATION | TR | Applicant | Round 2023-01 used for manufacturing Polyamide 6  |
| 2933 79 00 |  | 1818416/2022 | 2016 | (S)-2-amino-3-[(S)-2-oxopyrrolidin-3-yl]propanamide hydrochloride (CAS: 2628280-48-6) with a purity by weight of 98 % or more   | S | New | UNDER EXAMINATION | ES | Applicant | Round 2023/1 for use in the manufacturing of a new Active Pharmaceutical Ingredient   |
| 2933 79 00 |  | 1816558/2022 | 2012 | N-(n-octyl)-2-pyrrolidone (CAS RN 2687-94-7) with a purity by weight of 99 % or more  | S | New | UNDER EXAMINATION | BE | Applicant | Round 2023/1 for use in the manufacturing of fungicides   |
| 2933 79 00 |  | 2513786/2022 | 1092 | N-Methyl-2 Pyrrolidone - N-methyl prolidone with the following properties to be used in the manufacture of lithium-ion batteries with at least 99,9 % purity, not containing any metal impurities higher than                     | S | New | UNDER EXAMINATION | TR | Applicant | Round 2023/1  |

|            |  |              |      |   |   |     |                   |    |           |   |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
|            |  |              |      | 20 ppb and total water content below 400 ppm  |   |     |                   |    |           |   |
| 2933 99 80 |  | 2207020/2022 | 1081 | Benzotriazole-1-yl-oxy-tris-pyrrolidino-phosphonium hexafluorophosphate (CAS RN 12865-52-5) with a purity by weight of 97 % or more based on HPLC                     | S | New | UNDER EXAMINATION | DK | Applicant | Round 2023/1 used as a coupling reagent in a synthesis  |
| 2933 99 80 |  | 1848678/2022 | 1027 | (1R,2S,5S)-3-[(S)-3,3-dimethyl-2-(2,2,2-trifluoroacetamido)butanoyl]-6,6-dimethyl-3-azabicyclo[3.1.0]hexane-2-carboxylic acid with a purity by weight of 98 % or more | S | New | UNDER EXAMINATION | ES | Applicant | Round 2023/1 Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity). |
| 2933 99 80 |  | 1848735/2022 | 1026 | 7-(2-Methyl-4-nitrophenoxy)-[1,2,4]triazolo[1,5-a]pyridine (CAS RN 937263-44-0) with a purity by weight of 98 % or more   | S | New | UNDER EXAMINATION | ES | Applicant | Round 2023/1 Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity). |
| 2933 99 80 |  | 1578650/2022 | 1009 | (R)-2-(2,5-difluorophenyl)pyrrolidine hydrochloride (CAS RN 1218935-60-4) with a purity by weight of 98 % or more   | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 used for the production of a drug for the treatment of metastatic solid tumors                         |
| 2933 99 80 |  | 1848581/2022 | 1028 | 7-(2-Methyl-4-nitrophenoxy)-[1,2,4]triazolo[1,5-a]pyridine (CAS RN 937263-44-0) with a purity by weight of 98 % or more   | S | New | UNDER EXAMINATION | ES | Applicant | Round 2023/1 Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity). |
| 2933 99 80 |  | 1848488/2022 | 1029 | (1R,2S,5S)-3-[(S)-3,3-dimethyl-2-(2,2,2-trifluoroacetamido)butanoyl]-6,6-dimethyl-3-azabicyclo[3.1.0]hexane-2-carboxylic acid with a purity by weight of 98 % or more | S | New | UNDER EXAMINATION | ES | Applicant | Round 2023/1 Product used in the manufacturing of a new Active Pharmaceutical Ingredient (NCE New Chemical Entity). |
| 2934 99 90 |  | 2040968/2022 | 1044 | 4-[4-[(5s)-5-(Aminomethyl)-2-oxo-3-oxazolidinyl] phenyl]-3-morpholinone,  | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 Raw material used in the   |

|            |  |              |      |   |   |     |                   |    |           |   |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
|            |  |              |      | hydrochloride (CAS RN 898543-06-1) with a purity by weight of 98 % or more  |   |     |                   |    |           | synthesis of active pharmaceutical substance - Rivaroxaban  |
| 2934 99 90 |  | 1476593/2022 | 1002 | 2-(Trifluoromethyl)thioxanthen-9-one (CAS RN 850808-70-7) with a purity by weight of 98 % or more   | S | New | UNDER EXAMINATION | IT | Applicant | 2023/1 used for production of active ingredient   |
| 2934 99 90 |  | 1775912/2022 | 1015 | Uridine 5'-triphosphate trisodium salt (CAS RN 19817-92-6) with a purity by weight of 72 % or more  | S | New | UNDER EXAMINATION | ES | Applicant | Round 2023/1 is an intermediate of synthesis used in the manufacturing process of the active ingredient |
| 2934 99 90 |  | 1578826/2022 | 1011 | 2-Mercaptoadenosine (CAS RN 43157-50-2) with a purity by weight of 98 % or more   | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 used for the production of cangrelor a Antiplatelet (P2Y12 inhibitor)                      |
| 2934 99 90 |  | 2079651/2022 | 1051 | - Cytidine-phospho guanosin phosphorothioat Oligodeoxynucleotid CpG1018 (CAS RN 937402-51-2),<br>- solution, frozen,<br>- with a purity by weight of 75 % or more | S | New | UNDER EXAMINATION | AT | Applicant | Round 2023/1 for the production of human vaccines (e.g. HepatitisB, Covid19)                            |
| 2934 99 90 |  | 1808000/2022 | 2010 | 4H-Thieno[2,3-b]thiopyran-4-one,5,6-dihydro-6-methyl-, 7,7-dioxide, (6S) (CAS RN 148719-91-9) with a purity by weight of 98 % or more                             | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1<br><br>for use in the synthesis of intermediates and active pharmaceutical ingredients     |
| 2934 99 90 |  | 2207460/2022 | 1084 | 4-Methylmorpholine (N-Methylmorpholine – CAS RN 109-02-4) with a purity by weight of 99 % or more   | S | New | UNDER EXAMINATION | AT | Applicant | Round 2023/1<br>Chemical is used as raw material for the manufacturing of pharmaceutical intermediates  |
| 2935 90 90 |  | 2206421/2022 | 1076 | 5-(N-3-methylphenyl-sulfonylamido)-(N',N''-bis-(3-methylphenyl)-isophthalicacid-diamide) (CAS RN 2375645-78-4) with a purity by weight of 95 % or more            | S | New | UNDER EXAMINATION | NL | Applicant | Round 2023/1 Finished product is Thermosensitive media  |



|                          |  |              |      |   |   |     |                   |    |           |  |
|--------------------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
|                          |  |              |      |   |   |     |                   |    |           |  |
| 2935 90 90               |  | 1814824/2022 | 2011 | N-(3-{{5-(4-chlorophenyl)-1H-pyrrolo[2,3-b]pyridin-3-yl}carbonyl}-2,4-difluorophenyl)propanesulfonamide (CAS NR 918504-65-1) with a purity by weight of 98 % or more  | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 for use in the synthesis of intermediates and active pharmaceutical ingredients |
| 2940 00 00               |  | 2207590/2022 | 1087 | Methyl $\alpha$ -D-mannopyranoside (XAVA – CAS RN 617-04-9) with a purity by weight of 98 % or more   | S | New | UNDER EXAMINATION | AT | Applicant | Round 2023/1 used as auxiliary in the purification of an API                                 |
| 3208 20 10<br>3905 91 00 |  | 2206345/2022 | 1075 | Copolymer of vinylcaprolactam and vinylpyrrolidone (CAS RN 51987-20-3) in the form of a solution in 2-butoxyethanol (CAS RN 111-76-2) containing by weight 45 % or more but not more than 58 % of copolymer                   | S | New | UNDER EXAMINATION | NL | Applicant | Round 2023/1 used to lower the hydrate formation temperature of gas                          |
| 3824 99 92               |  | 1957046/2022 | 1030 | Solution containing:<br>- 30 % or more but not more than 40 % by weight of Lithium Hexafluorophosphate (CAS RN 21324-40-3) and<br>- 60 % or more but not more than 70 % by weight of Ethyl Methyl Carbonate (CAS RN 623-53-0) | S | New | UNDER EXAMINATION | CZ | Applicant | Round 2023/1 used to produce a special electrolyte for batteries for hi tech industries      |
| 3901 40 00               |  | 2002292/2022 | 1043 | LLDPE C4 pelletDensity: 0,924 g/cm3Melt index: from 18 to 22 g/10 min Peak Melting Temperature: 251 $^{\circ}$ F<br>Copolymer of ethylene with butene, without presence of octene or hexene                                   | S | New | UNDER EXAMINATION | ES | Applicant | Round 2023/1 to manufacture a Masterbatch with high loads of mineral filler                  |
| 3901 40 00               |  | 2002232/2022 | 1042 | LLDPE C4 pelletDensity: 0,926 g/cm3Melt index: from 48 to 52 50 g/10 min Peak Melting Temperature: 251 $^{\circ}$ F<br>Copolymer of ethylene with butene, without presence of octene or hexene                                | S | New | UNDER EXAMINATION | ES | Applicant | Round 2023/1 used to manufacture a Masterbatch with high loads of mineral filler             |
| 3903 90 90               |  | 2206531/2022 | 1078 | Mixture of polymers consisting by weight of:<br>- 10 % or more but not more than 30 % of a styrene-ethylene-butylene-styrene block copolymer (CAS RN 66070-58-4),   | S | New | UNDER EXAMINATION | NL | Applicant | Round 2023/1 used in an extrusion production line.   |

|            |  |              |      |   |   |     |                   |    |           |   |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
|            |  |              |      | <ul style="list-style-type: none"> <li>- 25 % or more but not more than 45 % of mineral oil (CAS RN 8042-47-5),</li> <li>- 25 % or more but not more than 45 % of calcium carbonate (CAS RN 1317-65-3),</li> <li>- 10 % or more but not more than 20 % of polypropylene (CAS RN 9003-07-0) and</li> <li>- 1 % or more but not more than 3 % of a copolymer of <math>\alpha</math>-methylstyrene and vinyltoluene (CAS RN 9017-27-0)</li> </ul>                        |   |     |                   |    |           |   |
| 3905 91 00 |  | 2206493/2022 | 1077 | Aqueous solution of a copolymer of vinylpyrrolidone and N,N-dimethylaminopropyl methacrylamide sulfate (CAS RN 175893-71-7), containing by weight 8 % or more, but not more than 12 % of copolymer  | S | New | UNDER EXAMINATION | NL | Applicant | Round 2023/1 Styleze CC-10 polymer is a copolymer of vinylpyrrolidone and dimethylaminopropyl methacrylamide, is a unique, patented polymer that delivers excellent hold and conditioning benefits to hair. |
| 3914 00 00 |  | 1578517/2022 | 1008 | Resina Ni Nitriloacetic acid Agrose   | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 used for the manufacture of drug for the treatment of diabetes and obesity.  |
| 3917 39 00 |  | 2207703/2022 | 1601 | Flexible pipes of PE-Xa or PPS, reinforced with aramid fiber layer, <ul style="list-style-type: none"> <li>- with an outer diameter from 25 mm to 160 mm,</li> <li>- suitable for a maximum operation pressure,</li> <li>- depending on construction type, of 1,0 MPa or 1,6 MPa and</li> <li>- maximum operating temperature depending on construction type, of 95°C, 115°C or 130°C,</li> </ul> for use in the district heating or district cooling networks<br>(1) | S | New | UNDER EXAMINATION | AT | Applicant | Round 2023-01 for use in the district heating or district cooling networks  |

|            |  |              |      |   |   |     |                   |    |           |  |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
| 3920 10 25 |  | 2513987/2022 | 1093 | Separator film;<br>- coated or uncoated with ceramic or polymer material,<br>- with a polyethylene content by weight of not more than 70 %,<br>- with an aluminum oxide content by weight of not more than 30 %,<br>- with a porosity of 30 % or more,<br>- with a total thickness of 5 µm or more but not more than 25 µm<br>for use in the manufacture of lithium-ion batteries<br>(1)  | S | New | UNDER EXAMINATION | TR | Applicant | Round 2023/1 for use in the manufacture of lithium-ion batteries   |
| 3920 62 19 |  | 2513606/2022 | 1091 | Non-transparent poly(ethylene terephthalate) film:<br>- coated on both sides with layers of organic substances on the basis of acryl of a thickness of 7 nm or more but not more than 80 nm,<br>- with a tensile strength of more than or equal to 300 N/cm (as determined by the ASTM D-882 method),<br>- with a total thickness of 200 µm or more but not more than 350 µm,<br>- with a width of 600 mm or more but not more than 1600 mm | S | New | UNDER EXAMINATION | TR | Applicant | Round 2023/1 used in production of solar panels for backside protection  |
| 4411 12 92 |  | 1987309/2022 | 1036 | Medium Density Fibreboard (MDF) with<br>- thickness 2,50 mm with tolerance $\pm 0,30$ mm,<br>- dimensions 1300 x 1100 mm or less,<br>- density of 0,95 g/cm <sup>3</sup> (HDF) or more,<br>- coated with melamine foil or lacquered on both sides,<br>- used for manufacturing of PCBs printed circuit boards<br>(1)  | S | New | UNDER EXAMINATION | SI | Applicant | Round 2023/1 made for the production of printed circuit boards are used only for drilling, for the process by which printed circuit boards are made. |
| 5407 30 00 |  | 2041406/2022 | 1046 | Fabric with an open structure consisting of polyolefin tapes, stacked one on top of the other and cross-linked with each other by a thermal method:<br>- containing of 99 % or more of HDPE,<br>- weighing of 21 g/m <sup>2</sup> or more but not more than 24 g/m <sup>2</sup> ,   | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in production of premium quality plastic packaging   |

|            |  |              |      |   |   |     |                   |    |           |  |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
|            |  |              |      | <ul style="list-style-type: none"> <li>- of a width of 560 mm or more but not more than 1200 mm,</li> <li>- of a thickness of 100 µm but not more than 120 µm,</li> <li>- an elongation to break MD 20 %,</li> <li>- an elongation to break CD 22 %,</li> <li>- with an MD stretch of 100 N / 5cm as determined by test method D882,</li> <li>- with a CD stretch of 130 N / 5cm as determined by test method D882</li> </ul> |   |     |                   |    |           |  |
| 7605 21 00 |  | 1866026/2022 | 1021 | Aluminium alloy wire, for the manufacture of aeronautical fasteners: <ul style="list-style-type: none"> <li>- of which the maximum cross-sectional dimension exceeds 7 mm, and</li> <li>- obtained by extrusion of billets then rolling mill process</li> </ul>   | S | New | UNDER EXAMINATION | FR | Applicant | Round 2023/1 The fasteners thus produced, according to aeronautical specifications and standards, are exclusively intended for aircraft                        |
| 7607 11 90 |  | 1659734/2022 | 1012 | Aluminium foil in rolls, not backed, rolled but not further worked, having a purity of 99.99 % by weight, with a width of 500 mm, with a surface oxide layer by 3 to 4 nm thick, and with a cubic texture of more than 95 %, of a thickness of not less than 0.03 mm but less than 0.2 mm, without internal layers of other material, in coils or in coiled strips  | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 to be processed into aluminum anode of electrolytic capacitors.   |
| 7607 11 90 |  | 1863122/2022 | 1025 | Aluminium foil in rolls: <ul style="list-style-type: none"> <li>- having a purity of 99.99 % by weight,</li> <li>- of a thickness of 0,021 mm or more but not more than 0,2 mm,</li> <li>- with a width of 500 mm,</li> <li>- with a surface oxide layer by 3 to 4 nm thick, and</li> <li>- with a cubic texture of more than 95 %</li> </ul>   | S | New | UNDER EXAMINATION | FR | Applicant | Round 2023/1 company manufactures and markets etched and anodized aluminum sheets used as anodes in Start-up and High Voltage aluminum electrolytic capacitors |
| 7607 11 90 |  | 1807685/2022 | 2008 | Aluminium foil in rolls, not backed, rolled but not further worked: <ul style="list-style-type: none"> <li>- with an aluminum purity by weight of 99,99 % or more,</li> <li>- of a thickness of not less than 0,03 mm but not more than 0,2 mm,</li> <li>- without internal layers of other material,</li> <li>- in coils or in coiled strips</li> </ul>  | S | New | UNDER EXAMINATION | IT | Applicant | Round 2023/1 for manufacture of top quality tab foil to be incorporated into high-end electrolytic capacitors  |

|            |  |              |      |   |   |     |                   |    |           |   |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
|            |  |              |      | for use as aluminum tab in the manufacture of capacitors (1)  |   |     |                   |    |           |   |
| 8407 90 10 |  | 2085044/2022 | 1066 | A power unit for garden machinery, with a two-stroke engine with: <ul style="list-style-type: none"> <li>- an output of 900 W or more, but not more than 1100 W,</li> <li>- a cylinder displacement of more than 24 cm<sup>3</sup> but not more than 30 cm<sup>3</sup>,</li> <li>- a rotation speed at maximum power of more than 8400 rpm but not more than 8600 rpm,</li> <li>- an idling speed of more than 2800 rpm but not more than 3200 rpm,</li> <li>- a fuel tank with a capacity of 0,5 l or more,</li> <li>- with a top bracket made of ADC12 aluminum or related,</li> <li>- with a shock absorber made of CR 12C plastic or related,</li> <li>- with a muffler made of stainless steel SUS310S or related,</li> <li>- with a shaft guard made of AZ91D magnesium alloy or related</li> </ul> | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in the manufacture of horticultural machinery |
| 8409 99 00 |  | 1987448/2022 | 1037 | Valve tappet of Chrome Molybdenum steel, with a top surface polished with a minimum hardness of 670 HV 0.3MIN, with: <ul style="list-style-type: none"> <li>- a weight of 35 g but not more than 39 g,</li> <li>- a diameter of 31,96 mm but not more than 31,98 mm,</li> <li>- a height of 22,8 mm but not more than 23,2 mm,</li> <li>- a length of 15,58 mm but not more than 16,52 mm</li> </ul>  | S | New | UNDER EXAMINATION | SE | Applicant | Round 2023/1 for production hybrid vehicle engine               |
| 8413 30 80 |  | 1776553/2022 | 1017 | Electric water pump ensuring the functionality of the water circuit also when the motor is temporarily switched off, for operating voltage of 9-16 V with: <ul style="list-style-type: none"> <li>- capacity - pressure 0,75 Bar at 3 800 rpm,</li> <li>- discharge of 12 LPM (liters per minute),</li> <li>- whether or not with connecting cable with connector,</li> <li>- mounting bracket</li> </ul>   | S | New | UNDER EXAMINATION | SK | Applicant | Round 2023/1 for production of cars                             |

|            |  |              |      |  |   |     |                   |    |           |  |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
|            |  |              |      | for use in the manufacture of goods of Chapter 87 (1)  |   |     |                   |    |           |  |
| 8501 10 99 |  | 2084077/2022 | 1057 | Worm axis motor for automotive electric seat adjustment applications: <ul style="list-style-type: none"> <li>- consisting of a permanently excited DC motor with a worm gear,</li> <li>- whether brushed or brushless,</li> <li>- whether or not with electronic controller unit,</li> <li>- whether or not with Hall Effect Sensor,</li> <li>- with a nominal voltage 8V or more but not more than 16V,</li> <li>- with a rated output mechanical power not exceeding 35W,</li> <li>- with a specified temperature range from -40°C to 160°C</li> </ul>                                     | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in the applicant's products have a direct application into seat functions        |
| 8501 10 99 |  | 2083368/2022 | 1053 | Linear actuator for automotive electric seat adjustment applications: <ul style="list-style-type: none"> <li>- consisting of a permanently excited DC motor with an integrated gear mechanism and leadscrew,</li> <li>- whether brushed or brushless,</li> <li>- whether or not with electronic controller unit,</li> <li>- whether or not with Hall Effect Sensor,</li> <li>- with a nominal voltage 8V or higher, but not higher than 16V,</li> <li>- with a rated output mechanical power not exceeding 20W,</li> <li>- with a specified temperature range from -40°C to 160°C</li> </ul> | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in the applicant's products have a direct application into seat functions        |
| 8501 10 99 |  | 2081056/2022 | 1052 | Rotary actuator for automotive electric seat adjustment applications: <ul style="list-style-type: none"> <li>- consisting of a permanently excited DC motor with an integrated gear mechanism,</li> <li>- whether brushed or brushless,</li> <li>- whether or not with electronic controller unit,</li> <li>- whether or not with Hall Effect Sensor,</li> <li>- with a nominal voltage 8V or more but not more than 16V,</li> </ul>   | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 motors used in the applicant's products have a direct application into seat functions |

|            |  |              |      |  |   |     |                   |    |           |   |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|---|
|            |  |              |      | <ul style="list-style-type: none"> <li>- with a rated output mechanical power not exceeding 35W,</li> <li>- with a specified temperature range from -40°C to 160°C</li> </ul>  |   |     |                   |    |           |   |
| 8501 10 99 |  | 2084298/2022 | 1059 | <p>Electric (DC) motor powered by height adjuster with 4-poles ferrite with:</p> <ul style="list-style-type: none"> <li>- a rated output mechanical power not exceeding 35 W,</li> <li>- frame integration with a length of 156 mm, a height of 59 mm, a thickness of 36 mm and a weight of 500 g,</li> <li>- a stall torque of 45 Nm and ultimate torque of 200 Nm,</li> <li>- a max current of 15 A,</li> <li>- no load speed of 7 RPM or more but not more than 10 RPM,</li> <li>- a rotation speed of 4000 RPM or more but not more than 5600 RPM,</li> <li>- a maximum noise level of 42 dB(A),</li> <li>- a maximum angular freewheel up to 3 degrees,</li> <li>- a 8 tooth pinion module</li> </ul> | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in the applicant's products have a direct application into seat functions |
| 8501 20 00 |  | 1863259/2022 | 1022 | <p>Universal electric motor, rotating, with a supply voltage of 230 V, with a power higher than 37,5 W but not exceeding 2000 W and a diameter of 98 mm, for the production of a torque to a transmission shaft for kitchen appliance</p>  | S | New | UNDER EXAMINATION | FR | Applicant | Round 2023/1 for production of Meat grinder, food processor                                 |
| 8501 20 00 |  | 1863184/2022 | 1024 | <p>Universal electric motor, rotating, with a supply voltage of 230 V, with a power higher than 37,5 W but not exceeding 1000 W and a diameter of 70 mm, for the production of a torque to a transmission shaft for kitchen appliance</p>  | S | New | UNDER EXAMINATION | FR | Applicant | Round 2023/1 for production of Chopper, blender   |
| 8501 20 00 |  | 1960824/2022 | 1032 | <p>Universal electric motor, rotating, with a supply voltage of 230 V, with a power higher than 37,5 W but not exceeding 700 W and a diameter of 54 mm, for the production of a torque to a transmission shaft for kitchen appliance</p>   | S | New | UNDER EXAMINATION | FR | Applicant | Round 2023/1 for producing grinder, small food processor, coffee grinder                    |

|            |  |              |      |  |   |     |                   |    |           |   |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|---|
| 8501 31 00 |  | 2084216/2022 | 1058 | Motors with a double output shaft for automotive electric seat adjustment applications:<br><ul style="list-style-type: none"> <li>- consisting of a permanently excited DC motor,</li> <li>- whether brushed or brushless,</li> <li>- whether or not with electronic controller unit,</li> <li>- whether or not with Hall Effect Sensor,</li> <li>- with a nominal voltage 8V or more but not more than 16V,</li> <li>- with a rated output mechanical power not exceeding 120W,</li> <li>- with a specified temperature range from -40°C to 160°C</li> </ul>                          | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in the applicant's products have a direct application into seat functions |
| 8501 51 00 |  | 2085129/2022 | 1067 | Electric AC motor, three phase permanent magnets, with:<br><ul style="list-style-type: none"> <li>- an output of 500 W or more but not more than 700 W,</li> <li>- an input power of 850 W or more but not more than 1000 W,</li> <li>- a rated power of 475 W or more but not more than 525 W,</li> <li>- an external diameter of 130 mm (<math>\pm</math> 0,3 mm) or more but not more than 180 mm (<math>\pm</math> 0,3 mm),</li> <li>- a rated speed of 16 000 rpm or more but not more than 17 000 rpm,</li> <li>- a weight of 2,5 kg or more but not more than 3,1 kg</li> </ul> | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used to manufacture home appliance products                                    |
| 8507 60 00 |  | 1961285/2022 | 2021 | A lithium-ion-rechargeable battery pack in a specific housing for use in digital still cameras, with:<br><ul style="list-style-type: none"> <li>- a length of 70 mm or more but not more than 120 mm,</li> <li>- a width of 60 mm or more but not more than 80 mm,</li> <li>- a height of 15 mm or more but not more than 45 mm,</li> <li>- a weight of 0,040 kg or more but not more than 0,085 kg, and</li> <li>- a capacity of not more than 1860 mAh</li> </ul>  | S | New | UNDER EXAMINATION | DE | Applicant | Round 2023/1 lithium batteries for use in digital still cameras                             |



## Gelen Tarih Sayı: 12/04/2022 - 1153

|            |  |              |      |  |   |     |                   |    |           |  |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| 8507 90 80 |  | 2207294/2022 | 1082 | Top cap made of ferrous alloy or stainless steel:<br>- whether or not including parts made of aluminum and aluminum alloy,<br>- with sealing elements or other elements made of polymer material,<br>- with a "current interrupt device" and an "evacuation valve",<br>- with an outer diameter between 17-18 mm<br>(1)  | S | New | UNDER EXAMINATION | TR | Applicant | Round 2023/1 is the mechanical raw material of the lithium-ion battery     |
| 8512 20 00 |  | 2085666/2022 | 1072 | Light guide for vehicles with:<br>- two parallel ribs in the front area with a distance between them of 1,4 mm or more but not more than 1,8 mm,<br>- four holes with the dimension of 7,3 mm or more but not more than 7,9 mm in the short direction of the guide,<br>- a 3 pines connector   | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used to highlight the deco in the door panel                  |
| 8512 20 00 |  | 2085728/2022 | 1073 | Lamp for vehicles with:<br>- a distance between integrated spring clip and surface of 0,85 mm or more but not more than 1,85 mm,<br>- a length of the housing to two front vertical ribs of 26,45 mm or more but not more than 26,75 mm,<br>- four horizontal ribs where the distance on the lower area over the base radia between the two is 18,5 mm or more but not more than 18,7 mm | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used to highlight the grab handle in door panel               |
| 8516 80 20 |  | 2083518/2022 | 1054 | Electric washing machine heating element with:<br>- a nominal output power of 1700 W at 230 V AC supply voltage,<br>- a weight of 230 g or more but not more than 250 g,<br>- a thickness of the external flange of 2 mm or more,<br>- isolation bushes of steatite or ceramic,<br>- no flat zones in the design   | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 In manufacture of home appliance products (washing machines). |
| 8537 10 91 |  | 2085252/2022 | 1068 | A control unit being a printed circuit board with:<br>- a microprocessor,<br>- a programmable memory,  | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used to manufacture home appliance products                   |

|            |  |              |      |  |   |     |                   |    |           |  |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
|            |  |              |      | <ul style="list-style-type: none"> <li>- a single connector,</li> <li>- a PPE housing,</li> <li>- a supply of voltage of 220V or more but not more than 240V,</li> <li>- a length of 200 mm or more but not more than 210 mm,</li> <li>- a width of 70 mm or more but not more than 100 mm,</li> <li>- a height of 20 mm or more but not more than 30 mm</li> </ul> <p>for use in the manufacture of dishwashers</p> <p>(1)</p>  |   |     |                   |    |           |  |
| 8537 10 91 |  | 1777373/2022 | 1018 | <p>Electronic control unit of the 360-degree vehicle situation display system with:</p> <ul style="list-style-type: none"> <li>- an operating voltage 9-16 V,</li> <li>- at least one connector,</li> <li>- whether or not with metal mounting bracket</li> </ul>  | S | New | UNDER EXAMINATION | SK | Applicant | Round 2023/1 for car production                                      |
| 8537 10 91 |  | 2083812/2022 | 1055 | <p>A control unit being a printed circuit board with:</p> <ul style="list-style-type: none"> <li>- a microprocessor,</li> <li>- a programmable memory,</li> <li>- a two or more connectors, but not more than twelve,</li> <li>- with or without LCD display,</li> <li>- with or without WiFi module,</li> </ul> <p>for use in the manufacture of built-in ovens</p> <p>(1)</p>  | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in manufacture of home appliance products (ovens). |
| 8537 10 98 |  | 2085447/2022 | 1070 | <p>A control unit being a printed circuit board with:</p> <ul style="list-style-type: none"> <li>- a microprocessor,</li> <li>- a two or more connectors but not more than four,</li> <li>- a modified resins,</li> <li>- a length of 180 mm or more but not more than 250 mm,</li> <li>- a width of 130 mm or more but not more than 200 mm,</li> <li>- a height of 40 mm or more but not more than 60 mm</li> </ul> <p>for use in the manufacture of washing machines</p> <p>(1)</p> | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in manufacture of home appliance products          |

## Gelen Tarih Sayı: 12/04/2022 - 1153

|            |  |              |      |   |   |     |                   |    |           |   |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
| 8537 10 98 |  | 2085361/2022 | 1069 | A control unit being a printed circuit board with:<br><ul style="list-style-type: none"> <li>- a microprocessor,</li> <li>- a two connectors,</li> <li>- a supply of voltage 215V or more, but not more than 245V,</li> <li>- no housing,</li> <li>- a length of 100 mm or more but not more than 120 mm,</li> <li>- a width of 40 mm or more but not more than 50 mm,</li> <li>- a height of 20 mm or more but not more than 30 mm</li> </ul> for use in the manufacture of refrigerators (1)  | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in manufacture of home appliance products                     |
| 8537 10 98 |  | 2083949/2022 | 1056 | A control unit being a printed circuit board with:<br><ul style="list-style-type: none"> <li>- a microprocessor,</li> <li>- eight or more connectors but not more than eleven,</li> <li>- a supply of voltage 215V or more but not more than 245V,</li> <li>- a housing of PA6-MR30,</li> <li>- a length of 280 mm or more but not more than 345 mm,</li> <li>- a width of 400 mm or more but not more than 470 mm,</li> <li>- a height of 28 mm or more but not more than 45 mm</li> </ul> for use in the manufacture of induction ovens (1) | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in manufacture of home appliance products (induction stoves). |
| 8538 90 99 |  | 2084836/2022 | 1064 | Control panel for mirror, windows and other functions in vehicles, with:<br><ul style="list-style-type: none"> <li>- a total length of 144 mm or more but not more than 150mm,</li> <li>- a distance between intended screwing interface center points of 31 mm or more but not more than 31,50 mm</li> </ul>   | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in manufacture of motor vehicles                              |
| 8538 90 99 |  | 2084930/2022 | 1065 | Single window regulator switch in vehicles, with:<br><ul style="list-style-type: none"> <li>- a total length of 52,25 or more but not more than 52,75 mm</li> <li>- a rear hole with the diameter in length direction of 5,4 mm or more but not more than 5,7 mm, and in side</li> </ul>  | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in manufacture of motor vehicles                              |

|            |  |              |      |  |   |     |                   |    |           |  |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
|            |  |              |      | direction of 4,4 mm or more but not more than 4,6 mm   |   |     |                   |    |           |  |
| 8538 90 99 |  | 2084836/2022 | 1060 | Control panel of a switch, made of PMMA with:<br>- a width of housing of 34,3 mm or more but not more than 34,9 mm,<br>- two center ribs on each side with a distance between them of 2,0 mm or more but not more than 2,2 mm  | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in manufacture of motor vehicles - blocking door switch    |
| 8538 90 99 |  | 2084573/2022 | 1061 | Control panel of a switch, made of PMMA with:<br>- a width of housing of 34,3 mm or more but not more than 34,9 mm<br>- two center ribs on each side with a distance between them of 2,0 mm or more but not more than 2,2 mm   | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in manufacture of motor vehicles - blocking door switch    |
| 8538 90 99 |  | 2085564/2022 | 1071 | Memory switch for vehicles, of PC, with:<br>- end stroke of 0,95 mm or more but not more than 1,25 mm,<br>- lock (button) rise with 5,7 (+/- 0,05) mm top surface,<br>- a width of 70,2 mm or more but not more than 70,8 mm,<br>- an outer dim of electric interface of 21,9 mm | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in manufacture of motor vehicles                           |
| 8538 90 99 |  | 2084759/2022 | 1063 | Housing of a memory switch control panel for vehicles with:<br>- a width of 70,2 mm or more but not more than 70,5 mm,<br>- parallel ribs with a distance between them of 2,6 mm or more but not more than 2,8 mm on the rear side,<br>- a 5 pines connector                     | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in manufacture of motor vehicles – memory switch           |
| 8538 90 99 |  | 2084675/2022 | 1062 | Control panel of a switch of central lock regulation in vehicles with:<br>- a main house width of 39,35 mm or more but not more than 39,95 mm,   | S | New | UNDER EXAMINATION | PL | Applicant | Round 2023/1 used in manufacture of motor vehicles - central lock regulation |

|               |    |                          |      |   |   |           |                   |                |   |  |
|---------------|----|--------------------------|------|---|---|-----------|-------------------|----------------|---|--|
|               |    |                          |      | - a 5 pines connector   |   |           |                   |                |   |  |
| 8544 42 90    |    | 1776432/2022             | 1016 | Connecting six core cable with three connectors, whether or not with a plastic clip to connect the oil pressure sensor in the differential and the differential actuator  | S | New       | UNDER EXAMINATION | SK             | Applicant                                 | Round 2023/1 for car production  |
| 8708 40 50    |    | 2001384/2022             | 1041 | Automatic transmission equipped with double clutch system with: <ul style="list-style-type: none"> <li>- at least 8 gears,</li> <li>- an engine torque equal to or greater than 800 Nm,</li> <li>- an electronic differential,</li> <li>- a P-lock safety system,</li> <li>- a TCU transmission control unit,</li> </ul> for use in the manufacture of motor vehicles of heading 8703<br>(1)  | S | New       | UNDER EXAMINATION | IT             | Applicant                                 | Round 2023/1 for production of cars  |
| ex 1515 90 99 | 92 | 1959/1/2002 PROLONG 2019 | 3500 | <b>DE(11.03.2022) request for amendment:</b><br><b>Microbial</b> oil, refined or semi-refined, containing by weight 35 % or more but not more than <b>70 %</b> of arachidonic acid or 35 % or more but not more than 50 % of docosahexaenoic acid<br><br>---<br><b>Current text:</b><br>Vegetable oil, refined or semi-refined, containing by weight 35 % or more but not more than 57 % of arachidonic acid or 35 % or more but not more than 50 % of docosahexaenoic acid | S | Amendment | UNDER EXAMINATION | IE<br>DE<br>ES | Applicant<br>Co-applicant<br>Co-applicant | Round 2023-01 - Request for amendment. Ingredient to manufacture infant formula nutritional products   |
| ex 3601 00 00 | 10 | 164630/2010 PROLONG 2022 | 3513 | <b>DE(11.03.2022) request for amendment:</b><br>Pyrotechnical powder in the form of granulate or cylindrical shape, composed of strontium nitrate or copper nitrate in the solution of nitroguanidine or <b>guanidine nitrate</b> , binder and additives, used as a component of airbag inflators (1)<br><br>---<br><b>Current text:</b>  | S | Amendment | UNDER EXAMINATION | PL             | Applicant                                 | Round 2023-01 - request for amendment. The material is used to manufacture gas generators for automobiles. The gas generators are used for Airbags |

|               |    |              |      |   |   |                  |                   |          |                      |  |
|---------------|----|--------------|------|---|---|------------------|-------------------|----------|----------------------|--|
|               |    |              |      | Pyrotechnical powder in the form of granulate of cylindrical shape, composed of strontium nitrate or copper nitrate in the solution of nitroguanidine, binder and additives, used as a component of airbag inflators<br>(1)   |   |                  |                   |          |                      |  |
| ex 3824 99 93 | 60 | 1427706/2018 | 3506 | <p><b>DE(11.03.2022) request for amendment:</b><br/>Mixture of phytosterols containing by weight:</p> <ul style="list-style-type: none"> <li>- 35 % or more but not more than 88 % Sitosterols,</li> <li>- 20 % or more but not more than 63 % Campesterols,</li> <li>- 14 % or more but not more than 38 % Stigmasterols,</li> <li>- not more than 13 % Brassicasterols,</li> <li>- <b>not more than 10 % other Stanols,</b></li> <li><b>and</b></li> <li>- <b>not more than 10 % other Sterols</b></li> </ul> <p>---</p> <p><b>Current text:</b><br/>Mixture of phytosterols (CAS RN 949109-75-5) in powder form containing by weight:</p> <ul style="list-style-type: none"> <li>- 40 % or more but not more than 88 % of sitosterols,</li> <li>- 20 % or more but not more than 63 % of campesterols,</li> <li>- 14 % or more but not more than 38 % of stigmasterols,</li> <li>- not more than 13 % brassicasterols,</li> <li><b>and</b></li> <li>- not more than 5 % sitostanols</li> </ul> | S | <b>Amendment</b> | UNDER EXAMINATION | DE       | Applicant            | <p>Round 2023-01 - request for amendment. ROUND 2019-01 accepted during 2nd ETQG meeting</p> <p>End use of imported goods: The main areas of application of the end products are contraception (birth control pills) and dermatology</p> |
| ex 3824 99 96 | 33 | 4834882/2018 | 3000 | <p>Buffer cartridge not exceeding 8000 ml containing:</p> <ul style="list-style-type: none"> <li>- 0,05 % or more but not more than 0,1 % by weight of 5-Chloro-2-methyl-2,3-dihydroisothiazol-3-one (CAS RN 55965-84-9) and</li> <li>- 0,05 % or more but not more than 0,1 % by weight of 2-Methyl-2,3-dihydroisothiazol-3-one (CAS RN 2682-20-4) as a biostatic</li> </ul>   | S | <b>Amendment</b> | UNDER EXAMINATION | UK<br>NL | Applicant<br>Opposed | <p>Round 2023-01 – NL propose to delete this suspension</p> <p>It is used in the manufacture of a DNA sequencing kit</p>   |

|  |  |                              |      |   |   |                  |                   |          |                      |  |
|--|--|------------------------------|------|---|---|------------------|-------------------|----------|----------------------|--|
| ex 7019 61 00<br>ex 7019 61 00<br>ex 7019 65 00<br>ex 7019 65 00<br>ex 7019 65 00<br>ex 7019 65 00<br>ex 7019 65 00<br>ex 7019 65 00<br>ex 7019 65 00<br>ex 7019 66 00<br>ex 7019 66 00<br>ex 7019 66 00<br>ex 7019 66 00<br>ex 7019 66 00<br>ex 7019 66 00<br>ex 7019 66 00<br>ex 7019 66 00<br>ex 7019 66 00<br>ex 7019 90 00<br>ex 7019 90 00 | 11<br>19<br>11<br>12<br>13<br>14<br>15<br>18<br>19<br>11<br>12<br>13<br>14<br>15<br>18<br>19<br>11<br>19 | 1122/2008<br>PROLONG<br>2019 | 3001 | Woven fabrics of rovings, impregnated with epoxy resin, with a coefficient of thermal expansion between 30°C and 120°C (measured according to IPC-TM-650) of:<br>- 10ppm per°C or more but not more than 12ppm per°C in the length and width, and<br>- 20ppm per°C or more but not more than 30ppm per°C in the thickness, with a glass transition temperature of 152°C or more but not more than 153°C (measured according IPC-TM-650) | S | <b>Amendment</b> | UNDER EXAMINATION | AT<br>EU | Applicant<br>Opposed | Round 2023-01 -<br>Objection.  |
| 7607 19 90   |  | 5691489/2021                 | 3003 | Aluminium foil in rolls with:<br>- an aluminium purity by weight of 99,99 % or more,<br>- a cubic texture of 95 % or more<br>- a leakage current of not more than 150 uA/C at 85 °C at forming factor 1,4, after 48-hour conditioning,<br>- a chloride content on the surface of not more than 0,5 mg/m <sup>2</sup> ,<br>for use as high-voltage anode foil in the manufacture of aluminium electrolytic capacitors<br>(1)             | S | <b>Amendment</b> | UNDER EXAMINATION | HU<br>EU | Applicant<br>Opposed | Round 2023-01- roll<br>over request.<br><br>for the manufacture of<br>aluminium electrolytic<br>capacitors |
| 7607 19 90   |  | 5691527/2021                 | 3004 | Aluminium foil in rolls with:<br>- an aluminium purity by weight of 99,99 % or more,<br>- an electrochemical anodized surface consisting of γ-aluminium(III) oxide with a thickness of not more than 300 nm,<br>- a chloride content on the surface of not more than 0,5 mg/m <sup>2</sup> ,<br>for use as low-voltage anode foil in the manufacture of aluminium electrolytic capacitors<br>(1)  | S | <b>Amendment</b> | UNDER EXAMINATION | HU<br>EU | Applicant<br>Opposed | Round 2023-01- roll<br>over request.<br><br>for the manufacture of<br>aluminium electrolytic<br>capacitors |
| 7607 19 90   |  | 5691437/2021                 | 3002 | Aluminium foil in rolls, with:  | S | <b>Amendment</b> | UNDER EXAMINATION | HU<br>EU | Applicant<br>Opposed | Round 2023-01- roll<br>over request.   |

|                                |          |              |      |   |   |                  |                   |          |                        |   |
|--------------------------------|----------|--------------|------|---|---|------------------|-------------------|----------|------------------------|---|
|                                |          |              |      | <ul style="list-style-type: none"> <li>- an aluminium purity by weight of 98 % or more,</li> <li>- an electrochemical anodized surface,</li> <li>- a chloride content on the surface of not more than 1 mg/m<sup>2</sup>,</li> </ul> <p>for use as cathode foil in the manufacture of aluminium electrolytic capacitors<br/>(1)</p>   |   |                  |                   |          |                        | for the manufacture of aluminium electrolytic capacitors<br><br>REJECTED                  |
| ex 8108 90 30                  | 55       | 4867502/2020 | 3507 | <p><b>FR(08.03.2022) request to remove the end-use requirement:</b><br/>Wires of an alloy of titanium:</p> <ul style="list-style-type: none"> <li>- with a niobium content by weight of 42 % or more but not more than 47 %,</li> <li>- with a diameter of not more than 6 mm,</li> <li>- complying with standard AMS 4982</li> </ul> <p>---</p> <p><b>Current text:</b><br/>Wires of an alloy of titanium:</p> <ul style="list-style-type: none"> <li>- with a niobium content by weight of 42 % or more but not more than 47 %,</li> <li>- with a diameter of not more than 6 mm,</li> <li>- complying with standard AMS 4982,</li> </ul> <p>for use in the production of aerospace fasteners<br/>(1)</p> | S | <b>Amendment</b> | UNDER EXAMINATION | FR       | Applicant              | Round 2023-01 - request for amendment.<br><br>Niobium titanium wire made of Niobium alloy |
| ex 8409 91 00<br>ex 8409 99 00 | 45<br>70 | 1378927/2017 | 3505 | <p><b>HU(14.03.2022) request for amendment:</b><br/>Metal alloy intake and exhaust valve, with a Rockwell hardness HRC 20 or more, for use in the manufacture of spark or compression ignition engines of motor vehicles (1)</p> <p>---</p> <p>Metal alloy intake and exhaust valve with a Rockwell hardness HRC 20 or more, but not more than HRC 50 for use in the manufacture of spark or compression ignition engines of motor vehicles<br/>(1)</p>   | S | <b>Amendment</b> | UNDER EXAMINATION | HU<br>SK | Applicant<br>Applicant | Round 2023-01 - request for amendment.<br><br>The intake and exhaust valve                |



|                                |          |                                |      |   |   |           |                   |          |                           |   |
|--------------------------------|----------|--------------------------------|------|---|---|-----------|-------------------|----------|---------------------------|---|
| ex 8409 91 00<br>ex 8409 99 00 | 50<br>55 | 371591/2013                    | 3508 | <p><b>DE(11.03.2022) request for amendment:</b><br/>Exhaust manifold with turbine housing of turbochargers:</p> <ul style="list-style-type: none"> <li>- used at an operating temperature of not more than 1 050 °C, and</li> <li>- with a hole to insert a turbine wheel, whereby the hole has a diameter of 28 mm or more, but not more than 181 mm</li> </ul> <p>---</p> <p><b>Current text:</b><br/>Exhaust manifold with turbine housing of turbochargers with:</p> <ul style="list-style-type: none"> <li>- a heat-resistance of not more than 1 050 °C, and</li> <li>- a hole to insert a turbine wheel, whereby the hole has a diameter of 28 mm or more, but not more than 181 mm</li> </ul> | S | Amendment | UNDER EXAMINATION | HU<br>AT | Applicant<br>Co-applicant | <p>Round 2023-01-requests for amendment.</p> <p>The turbine housing is a component of the turbocharger. The turbine housing transports the air to the turbine wheel, while increasing its energy through the spiral shape</p>         |
| ex 8411 99 00                  | 30       | 371591/2013<br>PROLONG<br>2022 | 3509 | <p><b>DE(11.03.2022) request for amendment:</b><br/>Turbine housing of turbochargers:</p> <ul style="list-style-type: none"> <li>- used at an operating temperature of not more than 1 050 °C, and</li> <li>- with a hole to insert a turbine wheel, whereby the hole has a diameter of 28 mm or more, but not more than 181 mm</li> </ul> <p>---</p> <p><b>Current text:</b><br/>Turbine housing of turbochargers with:</p> <ul style="list-style-type: none"> <li>- a heat-resistance of not more than 1 050 °C, and</li> <li>- a hole to insert a turbine wheel, whereby the hole has a diameter of 28 mm or more, but not more than 181 mm</li> </ul>   | S | Amendment | UNDER EXAMINATION | HU       | Applicant                 | Round 2023-01 - request for amendment.  |
| ex 8412 39 00                  | 20       | 371587/2013<br>PROLONG<br>2019 | 3514 | <p><b>DE(11.03.2022) request for amendment:</b><br/>Actuator for a single-stage turbocharger, with</p> <ul style="list-style-type: none"> <li>- -a pressure inlet pipe and a control rod with a working stroke of 15 mm or more but not more than 40 mm,</li> <li>- -a maximum length of the actuator including control rod of not more than 400 mm,</li> </ul>   | S | Amendment | UNDER EXAMINATION | HU       | Applicant                 | <p>Round 2023-01-request for amendment.</p> <p>The difference of the pressure delivered from the engine causes the membrane in the actuator to apply pressure to the spring. As a result, the conducting horn is removed from its</p> |

|               |    |              |      |  |   |                  |                   |    |           |   |
|---------------|----|--------------|------|--|---|------------------|-------------------|----|-----------|---|
|               |    |              |      | <ul style="list-style-type: none"> <li>- -a maximum diameter of the can at the widest point of not more than 140 mm, and</li> <li>- -a maximum height of the can without control rod of not more than 140 mm</li> </ul> <p>---</p> <p><b>Current text:</b><br/>Actuator for a single-stage turbocharger:</p> <ul style="list-style-type: none"> <li>- whether or not with conducting horns and connecting sleeves, having an operating distance of 20 mm or more but not more than 40 mm,</li> <li>- with a length of not more than 350 mm,</li> <li>- with a diameter of not more than 75 mm,</li> <li>- with a height of not more than 110 mm</li> </ul>   |   |                  |                   |    |           | position, thereby regulating the gas flow on the turbine side of the turbocharger. The actuator's zero point can be calibrated by turning the nut on the threaded rod |
| ex 8414 80 22 | 20 | 1564107/2017 | 3504 | <p><b>CZ(14.03.2022) request for amendment:</b><br/>Air membrane compressor with:</p> <ul style="list-style-type: none"> <li>- a flow of 4,5 l/min or more, but not more than 12 l/min,</li> <li>- power input of not more than 14 W, and</li> <li>- a gauge pressure capacity not exceeding 400 hPa (0,4 bar),</li> </ul> <p>of a kind used in the production of motor vehicle seats.</p> <p>----</p> <p><b>Current text:</b><br/>Air membrane compressor with:</p> <ul style="list-style-type: none"> <li>- a flow of 4,5 l/min or more, but not more than 7 l/min,</li> <li>- power input of not more than 8,1 W, and</li> <li>- a gauge pressure capacity not exceeding 400 hPa (0,4 bar),</li> </ul> <p>of a kind used in the production of motor vehicle seats</p> | S | <b>Amendment</b> | UNDER EXAMINATION | CZ | Applicant | Round 2023-01 - request for amendment. used to fill the bladder of the pneumatic seat comfort system.   |
| ex 8414 80 73 | 40 | 5001913/2020 | 3510 | <p><b>PL(11.03.2022) request for amendment:</b><br/>Hermetic heat pump compressor, for R134A or R450A as refrigerant:</p>  | S | <b>Amendment</b> | UNDER EXAMINATION | PL | Applicant | Round 2023-01 - request for amendment.  |

|               |    |              |      |   |   |                  |                   |    |           |  |
|---------------|----|--------------|------|---|---|------------------|-------------------|----|-----------|--|
|               |    |              |      | <ul style="list-style-type: none"> <li>- with the Single Phase Induction Motor PSC (Permanent Split Capacitor),</li> <li>- having bottom side suction connection and top side discharge connection,</li> <li>- with displacement 8,05 cm<sup>3</sup> or higher, but not higher than 8,25 cm<sup>3</sup>,</li> <li>- running at 2 800 rpm or faster, but not faster than 3 100 rpm,</li> <li>- with a cooling capacity of 920 W or higher, but not higher than 990 W in ASHRAE conditions</li> </ul> <p>---</p> <p><b>Current text:</b><br/>Hermetic heat pump compressor, for R134A or R450A as refrigerant:</p> <ul style="list-style-type: none"> <li>- with the Single Phase Induction Motor PSC (Permanent Split Capacitor),</li> <li>- having bottom side suction connection and top side discharge connection,</li> <li>- 8,1 cm<sup>3</sup> or 8,2 cm<sup>3</sup> displacement,</li> <li>- running at 3000 rpm,</li> <li>- with a cooling capacity of 920 W or higher, but not higher than 970 W in ASHRAE conditions</li> </ul> |   |                  |                   |    |           | For manufacture of household appliances. |
| ex 8501 20 00 | 30 | 1443120/2017 | 3503 | <p><b>DE(11.03.2022) request for amendment:</b><br/>Universal AC/DC motor with:</p> <ul style="list-style-type: none"> <li>- -a rated output of 50 W but not higher than 1,2 kW,</li> <li>- -a supply voltage of 230 V,</li> <li>- -also with engine brake,</li> <li>- -also assembled to a reduction gear with output shaft, which is contained in a housing</li> <li>- also fitted with a motor control/motor switch connected by cable</li> <li>- -also with fan,</li> </ul> <p>for use as electric drive of lawnmower blades or domestic appliances (1)</p> <p>---</p> <p><b>Current text:</b><br/>Universal AC/DC motor with</p>   | S | <b>Amendment</b> | UNDER EXAMINATION | AT | Applicant | Round 2023-01 - request for amendment.   |

|                                |          |                                |      |  |   |                  |                   |          |                           |   |
|--------------------------------|----------|--------------------------------|------|--|---|------------------|-------------------|----------|---------------------------|---|
|                                |          |                                |      | <ul style="list-style-type: none"> <li>- a rated output of 1,2 kW,</li> <li>- a supply voltage of 230 V, and</li> <li>- engine brake,</li> <li>- assembled to a reduction gear with output shaft, which is contained in a plastic housing</li> </ul> <p>for use as electric drive of lawnmower blades<br/>(1)</p>  |   |                  |                   |          |                           |   |
| ex 8529 90 92<br>ex 8548 00 90 | 15<br>60 | 837/2005<br>PROLONG<br>2019    | 3005 | <p>LCD modules,</p> <ul style="list-style-type: none"> <li>- solely consisting of one or more TFT glass or plastic cells,</li> <li>- not combined with touch screen facilities,</li> <li>- with one or more printed circuits boards with control electronics for pixel addressing only,</li> <li>- with or without backlight unit and</li> <li>- with or without inverters</li> </ul>  | S | <b>Amendment</b> | UNDER EXAMINATION | EU       | Applicant                 | Round 2023-01 - Objection.  |
| ex 8529 90 92                  | 55       | 816713/2014<br>PROLONG<br>2020 | 3006 | <p>OLED modules, consisting of</p> <ul style="list-style-type: none"> <li>- one or more TFT glass or plastic cells, containing organic material,</li> <li>- with or without combined touch screen facilities and</li> <li>- one or more printed circuit boards with control electronics for pixel addressing,</li> </ul> <p>for use in the manufacture of TV sets and monitors or for use in the manufacture of vehicles of Chapter 87<br/>(1)</p>   | S | <b>Amendment</b> | UNDER EXAMINATION | PL<br>BE | Applicant<br>Co-applicant | <p>Round 2023-01 - Objection.</p> <p>To be used in production of monitors and OLED TV sets. OLED module is protected by cover and is mounted in TV or monitor cabinet. It is connected with main PCB with a cable</p> |
| ex 8544 30 00<br>ex 8544 42 90 | 40<br>40 | 847787/2014<br>PROLONG<br>2020 | 3502 | <p>DE(11.03.2022) request for amendment:<br/>Wire harness or cable for steering system</p> <ul style="list-style-type: none"> <li>- -for an operating voltage of 12 V,</li> <li>- -with connectors on both sides,</li> <li>- -also with anchor clamps of plastic for mounting on a motor vehicle steering box</li> </ul> <p>---</p> <p>Current description:<br/>Wire harness of the steering system with an operating voltage of 12 V, equipped with connectors on both sides, having at least 3</p> | S | <b>Amendment</b> | UNDER EXAMINATION | SK       | Applicant                 | <p>Round 2023-01 - request for amendment.</p> <p>Sensor harness is used to connect the torque sensor with electro-motor in belt drive steering system.</p>  |

|  |  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  | plastic anchor clamps for mounting on a motor vehicle steering box |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1)